



ALNICO

Maße in mm. Änderungen vorbehalten.
 Standardmagnetisierung: Pfeilrichtung „M“
 Standardtoleranzen:
 Durchmesser: ca. 0.2 mm, Länge, Breite & Höhe: ca. 0.2 mm

STÄBE		BLOCK- & STÄBE			RINGE			HUFEISENFORM					
Durchmesser(D)	Länge(L)	Länge(l)	Breite(b)	Höhe(h)	Außend. (D)	Innend.(d)	Höhe (h)	A	B	C	D	E	F
2	max. 30	25,4	4,8	4,8	14,9	5	17	20	15	8	20	5,5	31
3	max. 200	32	6,3	6,3	20	8	30	11	10	12,5	10	-	35
3,5	max. 200	9,6	2	1	20	5	30	11	11	8	10	-	26/23,5
4	max. 200	25	6,3	6,3	25	9	12	12	10	10,5	12,5	-	21
5	max. 200	13,97	1,6	0,76	26	7,6	20	20	14	8,5	21	4	31
5,5	max. 200	44	25	17,5	30	7	25	25	18	11	26	5	40
6	max. 200	50	10	5	32	8	22	40	32	14	60	12	60
7	max. 200	50	15	10	32	15	24	20	15	7,5	20	4	30
7,9	25	60	12	5	34	7,5	25	25	20	10	25	5	40
8	max. 200	75	15	10	36	7,7	38	30	23	11	30	5	45
9	max. 200	100	15	10	48	7	40						
10	max. 200	100	30	13									
11	max. 200	150	15	10									
12	max. 200	200	15	10									
13	max. 200	130	30	30									
14	max. 200												
15	max. 200												
16	max. 200												
17	max. 200												
18	max. 200												
19	max. 200												
20	max. 200												