

E I DUPONT DE NEMOURS & CO INC

DUPONT POLYMERS, ENGINEERING POLYMERS NYLON RESINS PO BOX 80713,
CHESTNUT RUN PLAZA WILMINGTON DE 19880

Material Designation: **70G33L+**

Product Description: Polyamide 66 (PA66), glass reinforced, designated "Zytel" furnished as pellets.

| Color | Min. Thick. (mm) | Flame Class | HWI | HAI | RTI Elec | RTI Imp | RTI Str | IEC GWIT | IEC GWFI |
|--------------|-------------------------|--------------------|----------------|------------|-----------------|----------------|------------------|-----------------|-----------------|
| ALL | 0.71 | HB | 4 | 0 | 130 | 120 | 130 | - | - |
| | 1.5 | HB | 4 | 0 | 130 | 120 | 130 | - | - |
| | 3.0 | HB | 4 | 0 | 130 | 120 | 130 | - | - |
| | CTI: 0 | | HVTR: 1 | | D495: 5 | | IEC BP: - | | |

+ Virgin and Re grind from 1% to 50% by weight inclusive, have the same basic material characteristics.

NOTE (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "ZYT" or "MIN".

Report Date: 08/06/1996

Underwriters Laboratories Inc®

324299147

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.